
| Туре | | | |
|---------|--|--|--|
| Project | | | |
| Notes | | | |
| | | | |



AVL - LP8379





PRODUCT SPECIFICATIONS

| Model | AVL - LP 8379 | | | | |
|--------------------|--------------------------------------|--|--|--|--|
| Length | 600mm / 1200mm / 1800mm / 2400mm | | | | |
| Lumen Output | 75 lm/W | | | | |
| CRI | 80 or 90 | | | | |
| Voltage | 120 - 277V AC 347V AC | | | | |
| End Cap | Square Bevel | | | | |
| Colour Temperature | 3000k 3500k 4000k | | | | |
| Installation | Pendant Surface mounted Wall mounted | | | | |
| Beam Angle | 40 up 100 down | | | | |
| Certification | cETLus, CE, RoHS | | | | |
| Warranty | 5 years | | | | |











ORDER FORM

| LP8379 | | | | | | | | | | | | |
|---|----|----------------|------------------------------|-------------|----------|------------|------------------|--|-------|------------|---|---------------|
| 1 2 | 2 | 3 | } | 4 | 5 | 6 | 7 | 8 | 9 | 10 | П | OPTIONS |
| I. FAMILY | 2. | SIZE | | 3. | OUTPU | T LEVEL | 4 | . CRI | 5. EN | DCAP | 6. VO | LTAGE |
| LP8379 | | 6 | 600mm | | | m @ 6W / f | | 80 | | Bevel | | 100 - 277V AC |
| | | 12 18 24 | 1200mm 1800mm 2400mm | | | m @ 10 W / | | 90 | S | Square | 34 | 347V AC |
| 7. CCT | 8. | ССТ | - | 9. IN | ISTALLAT | ION | 10. C | OLOUR | | | II. DIMMI | NG |
| <i>Up</i> 30 3000K 35 3500K 40 4000K | | 35 | n 3000K 3500K 4000K | P S W | | mounted | 1 2 3 X | I Silver Powder Coated2 Black Powder Coated | | ed ited | ID No Dimming 2D 0-10V Dimming 3D TRIAC Dimming 4D DMX 5D Dali 6D Lutron Hi-Lume | |

OPTIONS

A 2 Circuit Wiring